ITALGRANITI GROUP

DECLARATION OF PERFORMANCE

No. 001 ITALGRANITI

Unique identification code of the product type:

Type, batch or serial number or any other element allowing identification of the product:

Dry-pressed ceramic tiles, with water absorption $E_{\rm v} \le 0.5$ %

2. Intended use(s):

For internal and external walls and floorings.

Name or registered trade mark, and contact address of the manufacturer:

ITALGRANITI GROUP SPA

Via Radici in Piano, 355 – 41043 Casinalbo di Formigine (MO) – Italy Tel. 0039 059 888411 Fax 0039 059 848808 P. iva e CF 03294200369

info@italgranitigroup.com www.italgranitigroup.com

System(s) of assessment and verification of constancy of performance (AVCP)

System 4

5. Name and identification number of notified laboratory, if relevant: N.A.

Task(s) carried out: N.A.

AVCP system: N.A.

Document issued and date of issue: N.A.

Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1+A1 _{fl}	
Release of dangerous substance, for		
 Cadmium 	NPD	
 Lead 	NPD	EN 14411
Breaking strength	> 1300 N	
Slipperiness, as:	Data available on request	
Tactility	NPD	
Bond strength/adhesion, for Cementitious adhesive, type C2	≥ 1·N/mm²	
Thermal shock resistance	Pass	
Durability for:	Vaccinities .	
• internal use	Pass	No.
 external use: freeze-thaw resistance 	Pass	

Tue performance of the product identified above is in conformity with the declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name and function Armando Bergamini Quality Supervisor

Place and date of issue Casinalbo, 2019-01-23

This documents of performance does not include decorative accessories, trim and mosaic

MARCATURA CE CE MARKING CE-KENNZEICHNUNG MARQUAGE CE MARCADO CE



ITALGRANITI GROUP SpA
Via Radici in Piano, 355 – 41043 Casinalbo di Formigine (MO) - Italy

05

001 ITALGRANITI

EN 14411

Dry-pressed ceramic tiles, with water absorption $E_{\nu} \leq 0.5\%$, for internal and external walls and floorings